



EBD Options & Accessories Terminations, Cables, Positioners

Termination Options:



- EBD-WALL**



White face plate
UL listed non-metallic bracket (LV-1/LV-2)
Available with either 1, 2, 3, 4, 6, or 12 ports
Individual port tagging is available
EBD-BLOCK available for unused ports

- EBD-301**



Concealed Ceiling Cup with cover-plate

Cover plate options:

Zinc (3" or 3.75")

White Primer Coated (3" or 3.75")

Stainless Steel (3" or 3.75")

See YR - 301 COVER PLATES for more information

- EBD-VM**




Hook-&-Loop Fastener to secure cable in preferred location.

Cable Options:

- EBDC**



"22/6" non-shielded plenum rated wire




One DELPHI (male) coupling
One RJ-12 (female) coupling

- EBDC-EXT**



"22/6" non-shielded plenum rated wire



One RJ-12 (male) coupling
One RJ-12 (female) coupling

Stocked lengths:

- EBDC-10 / EBDC-EXT- 10 (10')
- EBDC-25 / EBDC-EXT-25 (25')
- EBDC-50 / EBDC-EXT-50 (50')
- EBDC-75 / EBDC-EXT-75 (75')
- EBDC-100 / EBDC-EXT-100 (100')



Custom lengths up to 1,000' available
Individual wire tagging available

Positioner Options:

- EBDP (for EBD dampers)**



Hand-held battery power pack with male jack and LCD Blade indicator - (1) 9V battery included

- EBDLP (for EBDL dampers)**



Hand-held battery power pack with male jack and LCD Blade indicator - (3) 9V batteries included

Quantity	Option	Notes
PROJECT		LOCATION
CONTRACTOR		DESIGN SPECIFIER